

Product Parameter	
Tare Weight:	about 7.2 T;
Payload:	60 T;
Dimension (L*W*H):	12500mm*2500mm*1500mm;
Main beam:	500mm height, top plate 14mm thickness*140mm width, bottom plate 16mm thickness*140mm width, middle plate 8mm thickness;
Twist lock:	4+4/8/12 pcs, which could support 1×20” container, 2×20” containers or 1×40” container one time;
Platform:	3mm thickness checkered plate
King pin:	JOST 2.0/3.5 inches (bolted or welded);
Axles:	BPW/FUWA/ZY brand, 13T, 3pcs;
Suspensions:	Mechanical suspension (America type or German type);
Leaf springs:	10 layers 90mm*16mm, 6 units;
Tires:	11R22.5/12R22.5/11.00R20/12.00R20/315/80R22.5/385/65R22.5, 12pcs+1pc spare tire;
Rims:	9.0-22.5;
Landing gear:	JOST 28T, Linkage Outrigger;
Spare tire carrier:	1pc;
Tool box:	1 unit;
ABS:	Optional
Brake system:	WABCO 6 relays valve; T30/30+T30 air chamber, 40L air tanks;
Electric system:	One unit of 24V 7-pin ISO standard socket; with brake light, turn light, reverse light, side light, reflector, fog light; one set of 6-pin standard cable.
Accessories:	1 unit tool box, 1 pc spare tire carrier, all set of standard tools.
Others as the factory standard or according to the customer’ s requirements.	

