

Product Parameters:	
Shape:	Double D or Round shape
Dimension:	12300mm×2500mm×3800mm (The exact size depends on the final design and requirements from customers.)
Total Volume (m3):	45 m³
Compartments:	3 15,000L-15,000L-15,000L
Tanker Body Material:	5 mm thickness, Q345
End Plate:	6 mm thickness, Q345
Wave board:	5 mm thickness, Q345
Manhole Cover:	3pcs, 500mm(diameter), Europe type Aluminum alloy material
Bottom Valve:	3pcs, 4 inches Europe type subsea valve
Discharging Valve:	3pcs, 2.5 inches Europe type outlet
Discharging Pipe:	2.5" rubber hose, 2 pcs , 6m/each unit
Pump System:	Optional
Walkway:	Anti-skid walkway on top of the tank, with foldable handrail on both sides of the manhole covers.
Ladder:	Anti-skid access ladder fitted at front/back head of the tank.
Main Beams:	Welded design, Q345
Axle:	3 axles, 13 tons
Landing Gear:	JOST E100, double speed type
King Pin:	JOST 2.0 or 3.5 inches bolt-in king pin
Suspension:	Mechanical suspensions
Pneumatic Braking System:	WABCO RE 6 relay valve; Spring brake chamber (TKL brand); one piece of 45L air tank
Rim:	9.0-22.5, 13pcs
Tire:	Triangle brand 12R22.5, 13pcs
ABS:	Optional
Accessories:	One standard tool box, one spare tire carrier
Shipping Terms:	By bulk vessel

